

# CW -1.2K Metal Detector

# CW-1.2K

## Checkweigher with Metal Detector

- The CW-1.2K combines high-speed check weighing with metal detection for enhanced accuracy and safety.
- Features a 10-inch touch screen for easy operation and intuitive use.
- Includes external expansion options for IO ports, serial ports, and network communication, enabling comprehensive product management, monitoring and remote control.

**10-1200g**  
Weighing Range

**±0.7g**  
Accuracy

**100+Pcs/h**  
Speed

## Multiple Industrial Applications

- Food Industry
- Pharmaceuticals
- Daily Chemicals
- Textiles
- Manufacturing
- Packaging

### Metal Detection Sensitivity

Fe ≥ Φ 0.8mm

Sus304 ≥ Φ 2.0mm

Non-Fe ≥ Φ 1.5mm



+27 64 686 4952

info@titanautomation.co.za

www.titanautomation.co.za

# CW-1.2K Metal Detector


## Specification

Model	CW-1.2K
Weighing Range	100-1200g
Weighing Accuracy	±0.7g
Highest Weighing Speed	≤100pcs/min
Belt Speed	5-40 m/min
Belt Size	400x250mm
Belt Material	PU (White)
Structure of Material	304 Stainless Steel
Rejector	Optional: Swing Arm, Push Type and Air Blow
Metal Detection Sensitivity	Fe ≥ Φ 0.8mm Sus304 ≥ Φ 2.0mm non-Fe ≥ Φ 2.5mm
Metal Detector Wide	250mm
Metal Detector Height	Optional: 80mm/100mm/120mm/150mm/200mm
Platform Height	750±50mm
Operating Temperature	0-40°C
Maximum Humidity	90% R.H No Condensation
Limit Load	The instantaneous load shall not exceed 2.4kg

\*Metal detection sensitivity is related to test object features (humidity, temperature, salinity, mineral content, etc.), as well as some environmental effects, such as vibration, electromagnetic field interference, etc.

## Structure and Dimensions

Unit: mm



+27 64 686 4952

info@titanautomation.co.za

www.titanautomation.co.za